

# **SPIRENT GSS6700 WITH SIMGEN** FULLY FLEXIBLE MULTI-GNSS SIMULATION SYSTEM

The GSS6700 Multi-GNSS Simulator from Spirent has been developed for R&D, integration and verification testing of devices that use commercial GPS, GLONASS and/or Galileo signals.

### **Key Features**

- GPS/SBAS L1 C/A, GLONASS L1 C/A and Galileo E1 OS supported in a single chassis
- 12 channels of one, two or three GNSS constellations
- Complete scenario generation capability using Spirent's SimGEN for Windows® software
- Industry leading accuracy, fidelity and reliability
- Easily field upgradeable to add constellations
- Full user control of GPS constellation, signal errors and atmospheric effects
- Control of vehicle motion, antenna modeling, multipath and terrain obscuration modeling
- Interactive run time control
- Up to 4 GSS6700 chassis may be combined for supporting differential or attitude testing
- A GSS6700 configured with GPS supports SBAS signals (WAAS/EGNOS/MSAS) as standard
- Optional upgrades include:
  - GSS7765 Interference Simulation System
  - SimAUTO In-Vehicle Navigation System (IVNS) Solution
  - SimREMOTE for Hardware-in-the-Loop Testing
  - GSS4150 LAAS VDB Signal Simulator

The GSS6700 Multi-GNSS Constellation Simulator provides an easy-to-use but powerful solution for GNSS testing which can grow with your evolving needs. The Simulator provides 12 channels of one, two or three GNSS constellations in a single chassis and is easily upgradeable in the field to add constellations.

The GSS6700 is supplied pre-installed with Spirent's SimGEN for Windows® software suite. SimGEN offers comprehensive scenario generation capability including full user control of vehicle motion, satellite constellations, terrain obscuration, antenna patterns, multipath, atmospheric effects and error models.

A full range of hardware integration signals are provided for enhanced testing flexibility including: 1PPS input and output, external reference clock input, 10 MHz output and hardware trigger.

A single SimGEN computer may control multiple GSS6700 chassis for generating up to four independent RF outputs to support applications with multiple vehicles or multiple antennas.

All of our equipment is manufactured in an ISO 9001 certified facility and is provided with a 12 month warranty that may be extended with a support contract to maximize your investment. Our customer support facility offers comprehensive support and includes 25 years of experience in satellite navigation testing.

Please contact us for further information. We will be pleased to discuss your specific requirements and arrange a demonstration.

Multi-GNSS Simulation System: Spirent GSS6700 with SimGEN

## **SPIRENT GSS6700 with SimGEN** FULLY FLEXIBLE MULTI-GNSS SIMULATION SYSTEM

1575.42MHz

1575.42MHz

1602MHz

±600m/s

±45m/s<sup>2</sup>

±50m/s<sup>3</sup>

zero

±0.002m RMS

±0.001m/s RMS

## **SPECIFICATION**

#### **Output Frequency**

- GPS L1GLONASS L1 (Ch
- GLONASS L1 (Ch0)Galileo E1

## **Signal Dynamics**

Max Velocity\*
Max Acceleration\*
Max Jerk\*


#### **Signal Accuracy**

- Pseudorange
- Pseudorange rate
- Interchannel bias

#### **Signal Quality**

0	Spurious (Max)	-30dBc
0	Harmonics (Max)	-40dBc
0	Phase Noise (Max)	0.02 rad RMS
0	Frequency Stability	±1 x 10 <sup>-8</sup> over temp range

\* Higher dynamics can be achieved at a slight reduction in accuracy. Please contact Spirent for more information.



SimGEN for Windows<sup>®</sup> User Interface

#### Signal Level O GPS/SBAS L1 C/A

GLONASS L1 C/A -131dBm nominal 0 -128.5dBm nominal Galileo E1 OS 0 **Signal Level Control** +15/-20dB 0 Range Ο Resolution 0.1dB 0 Accuracy ±1.0dB RSS **Signal Generator Unit** 0 Channel type 12 GPS L1 C/A with SBAS

-130dBm nominal

(independent) and/or 12 GLONASS L1 C/A and/or 12 Galileo E1 OS • Size (W x D x H) 449 x 386 x 89mm (17.75 x 15.25 x 3.5in) • Weight 6.5kg (14.5 lbs) • Power 100 - 240 V AC

## Product Specification (MS3067) is available on request.

Performance figures and data in this document are provisional and must be specifically confirmed in writing by Spirent Communications plc before they become applicable to any particular order or contract.

50 – 60 Hz

The publication of information in this document does not imply freedom from patent or other rights of Spirent Communications plc. or others.

For current product data, visit the Spirent websites at www.spirent.com/positioning or www.spirentfederal.com

EUROPE AND THE MIDDLE EAST +44 1803 546325 globalsales@spirent.com www.spirent.com/positioning

AMERICAS + 1 714 692 6565 info@spirentfederal.com www.spirentfederal.com



© 2009 Spirent Communications, Inc. All of the company names and/or brand names and/or prouct names referred to in this document, in particular the name "Spirent" and its logo device, are either registered trademarks or trademarks pending registration in accordance with relevant national laws. All rights reserved. Specifications subject to change without notice. Rev. E 06/09